

SFI Specifications applicable to WDRA Drag Racing, with respective expiration periods. An item with an expiration period must be inspected and recertified at the end of this period before it can be used to qualify at a WDRA event. Specifications are available from the SFI Foundation. www.sfifoundation.com - 858.451.8868

| SPEC. NO. | DESCRIPTION   | EXPIRATION |
|-----------|---|------------|
| 1.1       | Replacement Flywheels and Clutch Assemblies                 | 2 Years    |
| 1.2       | Multiple Disc Clutch Assemblies                             | 2 Years    |
| 1.4       | Alcohol Drag Race Multiple Disc Clutch Assemblies           | 1 Year     |
| 1.5       | Multiple Disc Clutch Assemblies for Supercharged,           |            |
|           | Nitrous Oxide-injected, and Turbocharged Vehicles           | 1 Year     |
| 2.1       | Rear Engine Dragster Roll Cage - 6.29 and quicker           | 2 Years    |
| 2.2       | Front Engine Dragster Roll Cage - 6.29 and quicker          | 2 Years    |
| 2.3       | Rear Engine Dragster Roll Cage - Top Fuel Entries           | 2 Years    |
| 2.4       | Front Engine Dragster Roll Cage - 6.30 to 7.49 Seconds      | 2 Years    |
| 2.5       | Rear Engine Dragster Roll Cage - 6.30 to 7.49 Seconds       | 2 Years    |
| 2.6       | Front Engine Dragster Roll Cage - 7.50 Seconds & Slower     | 3 Years    |
| 2.7       | Rear Engine Dragster Roll Cage - 7.50 Seconds & Slower      | 3 Years    |
| 3.2       | Fire Protection Material (Technical Bulletin)               | N/A        |
| 3.2A      | Driver Suits/1/3/5  | N/A        |
| 3.2A      | Driver Suits/10/15/20 /25/30                                | 5 Years    |
| 3.3       | Driver Accessories  | N/A        |
| 4.1       | Automatic Transmission Shields (rigid)                      | 5 Years    |
| 4.1       | Automatic Transmission Shields (flexible)                   | 2 Years    |
| 6.1       | Containment Bellhousing for SFI 1.1 & 1.2 two disc max      |            |
|           | Clutch Assemblies used only on naturally aspirated vehicles | 5 Years    |
| 6.2       | Bellhousing for SFI 1.2, 1.3,1.4 &1.5 Clutch Assemblies     | 2 Years    |
| 6.3       | Bellhousing for SFI 1.2, 1.3 & 1.4 Clutch Assemblies        | 2 Years    |
| 7.1       | Lower Engine Containment Device                             | 1 Year     |
| 7.2       | Lower Engine Containment Device                             | 5 Years    |
| 8.1       | Remote Fuel System Drive Assembly                           | N/A        |
| 9.1       | Front Wheel Drive Vehicle Bellhousing Shields               | 5 Years    |
| 10.1      | Funny Car Roll Cage   | 2 years    |
| 10.2      | Funny /Altered Car Roll Cage 6.00 to 7.49                   | 2 years    |
| 10.3      | Funny /Altered Car Roll Cage 7.49 and slower                | 3 years    |
| 10.4      | Side Steer Roadster 7.49 and slower                         | 3 years    |
| 14.1      | Supercharger Restraint Devices                              | 2 Years    |
| 14.2      | Alcohol Supercharger Restraint Devices                      | 2 Years    |
| 14.21     | Screw-Type Supercharger Restraint Devices                   | 2 Years    |
| 14.4      | Containment Valve Covers/Valve Cover Shields                | 2 Years    |
| 15.1      | Drag Race Drive Wheels                                      | N/A        |
| 15.2      | Drag Race Front Wheels                                      | N/A        |
| 15.3      | Drag Race Drive Wheels                                      | N/A        |
| 15.4      | Drag Race Drive Wheels                                      | N/A        |
| 16.1      | Driver Restraint Assemblies                                 | 2 Years    |
| 16.5      | Driver Restraint Assemblies                                 | 2 Years    |
| 17.1      | On Board Fire Extinguishing Systems                         | N/A        |
| 18.1      | Crankshaft Hub Harmonic Dampers                             | N/A        |

| 23.1<br>24.1 | Supercharger Pressure Relief Assemblies<br>Youth Helmets                               | 2 Years<br>N/A |
|--------------|--|----------------|
| 25.1         | Full Bodied Car, Tube Chassis Roll Cage - 7.49 Seconds and Quicker; 2,800 Lbs. Maximum | 2 Years        |
| 25.2         | Full Bodied Car, Tube Chassis Roll Cage - 7.49 Seconds and Quicker; 3,200Lbs. Maximum  | 2 Years        |
| 25.3         | Full Bodied Car, Tube Chassis Roll Cage - 6.50 Seconds and Slower; 3,600 Lbs. Maximum  | 2 years        |
| 25.4         | Full Bodied Car Tube Chassis Roll Cage - 7.50 to 8.49 Seconds;                         | z years        |
|              | 3,600 Maximum  | 3 Years        |
| 25.5         | Full Bodied Car Stock or Modified/OEM Floor and Firewall                               |                |
|              | with OEM Frame or Uni-Body Construction - 7.50 to 8.49 Secon                           | ds;            |
|              | 3,600 Lbs. Maximum   | 3 Years        |
| 27.1         | Window Nets (Mesh)   | 2 Years        |
| 27.1         | Window Nets (Ribbon)   | NA             |
| 28.1         | Fuel Cells   | N/A            |
| 29.1         | Automatic Transmission Flexplates  | 3 Years        |
| 30.1         | Automatic Transmission Flexplate Shields   | 5 Years        |
| 31.1         | Flame Resistant Open Face Motorsport Helmets (SA)                                      | N/A            |
| 31.2         | Flame Resistant Closed Face Motorsport Helmets (SA)                                    | N/A            |
| 34.1         | Screw-Type Superchargers   | 3 Years        |
| 37.1         | Roll Cage Nets   | N/A            |
| 38.1         | Head and Neck Restraint System   | N/A            |
| 40.1         | Abrasion Resistant Driver/Rider Suites   | N/A            |
| 41.1         | Open Face Motorsport Helmets SN (M Rating)   | N/A            |
| 41.2         | Closed Face Motorsport Helmets SN (M Rating)   | N/A            |
| 42.1         | Steering Wheel Quick Disconnect/Release  | N/A            |
| 43.1         | Driveshaft   | N/A            |
| 45.1         | Roll Cage Padding  | N/A            |
|              |  |                |